

# CDM

# 50Hz

# CDMF

## Light Vertical Multistage Centrifugal Pump



Stock code:300145

**Pumping Water Pumping Honor**

**CNP**





## Company profile

Founded in 1991, CNP has been listed on Shenzhen Stock Exchange on 9th December, 2010; Stock name: CNP; Stock code: 300145

In 2017, CNP's annual output has exceeded 700,000 units/set, with sales over 2 billion, and continues to grow at a double-digit annual rate. CNP has a national-level enterprise technology center, launched ultra-high efficient, new generation CDM (F) light vertical multi-stage centrifugal pump in 2017. All series of light stainless steel pump products grow stably. Advanced frequency conversion water supply equipment has been innovated to the 6th generation. Fire pump and diesel engine have obtained UL certification. TD in-line pump, NIS/ NISO end suction pump, NSC split casing pump, WQ sewage pump, metering pump, oil pump and other pump products, can meet various application needs of different fields.

With over 300 domestic offices and foreign agents, CNP has a complete network of marketing services to meet the requirements of overseas and domestic needs. The products have been widely applied in the area of pressurization, industry, living water, cycling of air-conditioning water, heat supply, fire extinguishing system, pumping of underground water, treatment of sewage and waste water, chemical industry and desalination of sea water, etc.

CNP, a green water expert beside you.


**PUMPINGS.STORE : 096-385-8065**

# Contents

|                                                        |    |
|--------------------------------------------------------|----|
| Performance scope.....                                 | 1  |
| Performance range.....                                 | 2  |
| Summary.....                                           | 3  |
| Motor.....                                             | 3  |
| Working conditions.....                                | 3  |
| Application.....                                       | 3  |
| Performance curve.....                                 | 3  |
| Model definition.....                                  | 4  |
| Max.working perssure.....                              | 5  |
| Min.inlet pressure.....                                | 5  |
| Max ambient temperature, altitude above sea level..... | 5  |
| CDM/CDMF 1,3,5 Sectional drawing.....                  | 6  |
| CDM/CDMF 10,15,20 Sectional drawing .....              | 7  |
| CDM/CDMF 32,42,65,85 Sectional drawing.....            | 8  |
| CDM/CDMF 120,150,200 Sectional drawing.....            | 9  |
| CDM/CDMF 1 Performance curve.....                      | 10 |
| CDM/CDMF 1 Performance table .....                     | 11 |
| CDM/CDMF 3 Performance curve.....                      | 12 |
| CDM/CDMF 3 Performance table .....                     | 13 |
| CDM/CDMF 5 Performance curve.....                      | 14 |
| CDM/CDMF 5 Performance table .....                     | 15 |
| CDM/CDMF 10 Performance curve.....                     | 16 |
| CDM/CDMF 10 Performance table.....                     | 17 |
| CDM/CDMF 15 Performance curve.....                     | 18 |
| CDM/CDMF 15 Performance table.....                     | 19 |
| CDM/CDMF 20 Performance curve.....                     | 20 |
| CDM/CDMF 20 Performance table.....                     | 21 |
| CDM/CDMF 32 Performance curve.....                     | 22 |
| CDM/CDMF 32 Performance table.....                     | 23 |
| CDM/CDMF 42 Performance curve.....                     | 24 |
| CDM/CDMF 42 Performance table.....                     | 25 |
| CDM/CDMF 65 Performance curve.....                     | 26 |
| CDM/CDMF 65 Performance table.....                     | 27 |
| CDM/CDMF 85 Performance curve.....                     | 28 |
| CDM/CDMF 85 Performance table.....                     | 29 |
| CDM/CDMF 120 Performance curve.....                    | 30 |
| CDM/CDMF 120 Performance table.....                    | 31 |
| CDM/CDMF 150 Performance curve.....                    | 32 |
| CDM/CDMF 150 Performance table.....                    | 33 |
| CDM/CDMF 200 Performance curve.....                    | 34 |
| CDM/CDMF 200 Performance table.....                    | 35 |
| CDM/CDMF 1 Installation sketch.....                    | 36 |
| CDM/CDMF 3 Installation sketch.....                    | 37 |
| CDM/CDMF 5 Installation sketch.....                    | 38 |
| CDM/CDMF 10 Installation sketch.....                   | 39 |
| CDM/CDMF 15 Installation sketch.....                   | 40 |
| CDM/CDMF 20 Installation sketch.....                   | 41 |
| CDM/CDMF 32 Installation sketch.....                   | 42 |
| CDM/CDMF 42 Installation sketch.....                   | 43 |
| CDM/CDMF 65 Installation sketch.....                   | 44 |
| CDM/CDMF 85 Installation sketch.....                   | 45 |
| CDM/CDMF 120 Installation sketch.....                  | 46 |
| CDM/CDMF 150 Installation sketch.....                  | 47 |
| CDM/CDMF 200 Installation sketch.....                  | 48 |



Performance scope



## Performance range

| Description         |                       | CDM/CDMF   |           |           |           |           |           |
|---------------------|-----------------------|------------|-----------|-----------|-----------|-----------|-----------|
| Rated flow [m³/h]   |                       | 1          | 3         | 5         | 10        | 15        | 20        |
| Rated flow [l/s]    |                       | 0.28       | 0.83      | 1.39      | 2.78      | 4.17      | 5.56      |
| Flow range [ m³/h]  |                       | 0.5~2.4    | 1.2~4.4   | 2.5~8.5   | 5~14      | 8~24      | 10~29     |
| Flow range [l/s]    |                       | 0.14~0.67  | 0.33~1.22 | 0.69~2.36 | 1.39~3.89 | 2.22~6.67 | 2.78~8.06 |
| Max. pressure [bar] |                       | 22         | 23        | 24        | 24        | 22        | 25        |
| Motor power [kW]    |                       | 0.37~2.2   | 0.37~3    | 0.37~5.5  | 0.75~11   | 1.1~15    | 1.1~18.5  |
| Temp [°C ]          |                       | -15 ~ +120 |           |           |           |           |           |
| Max. efficiency [%] |                       | 48         | 58        | 70        | 72        | 73        | 73        |
| CDM<br>Pipelines    | DIN flange            | DN25       | DN25      | DN32      | DN40      | DN50      | DN50      |
|                     | Oval flange           | G1         | G1        | G1¼       | G1½       |           |           |
| CDMF<br>Pipelines   | DIN flange            | DN25       | DN25      | DN32      | DN40      | DN50      | DN50      |
|                     | Cutting ferrule joint | DN32       | DN32      | DN32      | DN50      | DN50      | DN50      |
|                     | Pipe thread           | R1¼        | R1¼       | R1¼       | R2        | R2        | R2        |
|                     | Oval flange           | G1         | G1        | G1¼       | G1½       |           |           |

| Description         |            | CDM/CDMF   |            |            |             |             |          |
|---------------------|------------|------------|------------|------------|-------------|-------------|----------|
| Rated flow [m³/h]   |            | 32         | 42         | 65         | 85          | 120         | 200      |
| Rated flow [l/s]    |            | 8.89       | 11.67      | 18.06      | 23.61       | 33.33       | 55.56    |
| Flow range [ m³/h]  |            | 16~40      | 25~55      | 30~80      | 50~110      | 60~150      | 80~180   |
| Flow range [l/s]    |            | 4.44~11.11 | 6.94~15.28 | 8.33~22.22 | 13.89~30.56 | 16.67~41.67 | 22.22~50 |
| Max. pressure [bar] |            | 29         | 30         | 22         | 17          | 16          | 16       |
| Motor power [kW]    |            | 1.5~30     | 3~45       | 4~45       | 5.5~45      | 11~75       | 11~75    |
| Temp [°C ]          |            | -15~+120   |            |            |             |             |          |
| Max. efficiency [%] |            | 73         | 75         | 76         | 77          | 74          | 73       |
| Pipelines           | DIN flange | DN65       | DN80       | DN100      | DN100       | DN125       | DN125    |
|                     |            |            |            |            |             |             | DN150    |

---

## Summary

CDM/CDMF pumps are new generation, high efficiency, non-self-priming vertical multistage centrifugal pumps (Abbr. as pumps). It referred European standard, used entirely new industrial design. It is energy saving, low noise, environment friendly, compact design, beautiful shape, light, easy for service, high reliability.

---

## Motor

Totally enclosed, fan cooled, 2 pole standard motor  
IP class: IP55

Insulation class: F

Voltage: 50Hz: 1×200-230/240V  
3×200-220/346-380V  
3×220-240/380-415V

---

## Working conditions

Thin, clean, non-flammable, non-explosive, solid free, fiber free, physically and chemically water-like liquid.

Liquid temperature:

Normal temperature type: -15°C to 70°C

Hot water type: -15°C to 120°C

Ambient temperature: up to +40°C

Altitude: up to 1000m

---

---

## Application

CDM/CDMF pumps are designed for a variety of applications from the pumping of potable water to the pumping of industrial liquids. Applied for liquids of different temperature, different rated flow, different pressure range. CDM is suitable for non-corrosive liquid, CDMF is suitable for light corrosive liquid.

Boosting: Filtering and transferring water in water factories, delivering water in different zone, pressuring for major pipelines, boosting for high buildings.

Pressuring: Water circulating system, washing system, high pressure flushing system, fire-fighting system.

HVAC: Air condition system

Water treatment: Ultrafiltration system, R/O system, distillation system, separator, swimming pool.

---

## Performance curve

Following conditions are suitable for performance curve below.

1. All curves are based on the measured values of 50Hz; constant motor speed 2900rpm or 2950rpm.

2. Curve tolerance in conformity with ISO9906:2012, Grade 3B.


3. Measurement is done with 20°C air-free water, kinematic viscosity of 1mm<sup>2</sup>/sec.

4. The operation of pump shall refer to the performance region indicated by the thickened curve to prevent overheating due to too small flow rate or overload of motor due to too large flow rate.


---

## Model definition


CDM/CDMF 1,3,5,10,15&20



CDM/CDMF 32,42,65,85,120&150



CDM/CDMF 200




## Max.working perssure

| Model                                                       | Max working(bar) |
|-------------------------------------------------------------|------------------|
| CDM/CDMF1,3,5,10,15,20 Flange, cutting ferrule, pipe thread | 25               |
| CDM/CDMF1,3,5,10 oval flange                                | 16               |
| CDM32                                                       |                  |
| 32-1-1~32-8                                                 | 16(30)           |
| 32-9-2~32-16                                                | 30               |
| CDMF32                                                      | 30               |
| CDM42                                                       |                  |
| 42-1-1~42-6-2                                               | 16(30)           |
| 42-6~42-9                                                   | 25(30)           |
| 42-10-2~42-13-2                                             | 30               |
| CDMF42                                                      |                  |
| 42-1-1~42-9                                                 | 16(25)           |
| 42-10-2~42-13-2                                             | 25               |
| CDM65                                                       |                  |
| 65-1-1~65-5-2                                               | 16(25)           |
| 65-5-1~65-8-1                                               | 25               |
| CDM85                                                       |                  |
| 85-1-1~85-4-2                                               | 16(25)           |
| 85-4~85-6                                                   | 25               |
| CDMF65,85                                                   | 25               |
| CDM/CDMF120,150,200                                         | 20               |

( )Need to specify especially.

## Max ambient temperature, altitude above sea level

When pumps working in the condition of higher than 40°C or higher than 1000m altitude, because the air density lessened, cooling performance is reduced, motor output power  $P_2$  is reduced also. The motor power shall be enlarged in those working conditions.



## Min.inlet pressure

In case that the pressure in pump is lower than the steam pressure used to convey liquid, the cavitations will occur. To avoid cavitations, a minimum pressure at the inlet side of the pump shall be guaranteed. The maximum suction stroke can be calculated with following formula:

$$H = P_b \times 10.2 - \text{NPSH} - H_f - H_v - H_s$$

$P_b$  = Barometric pressure in bar.

(Barometric pressure can be set to 1 bar).

In a closed system,  $P_b$  means system pressure [bar].

NPSH = Net Positive Suction Head [m].

(It can be read from the point of possible max. flow rate shown on NPSH curve.)


$H_f$  = Pipe friction loss at the inlet [m].

$H_v$  = Vapour pressure [m].

$H_s$  = Safety margin = minimum 0.5 meters head.



If the "H" calculated is positive, the pump may run under the max. suction stroke H.

If the "H" calculated is negative, A head of minimum inlet pressure H is required.





## CDM/CDMF 1,3,5 Sectional drawing



### CDM 1,3,5 Material list


| Pos. | Name                   | Materials                          | AISI/ASTM |
|------|------------------------|------------------------------------|-----------|
| 1    | Motor                  |                                    |           |
| 2    | Pump head              | Cast iron                          | ASTM25B   |
| 4    | Mechanical seal        | Tungsten carbide /Carbon           |           |
| 5    | Top diffuser           | Stainless steel                    | AISI304   |
| 6    | Diffuser               | Stainless steel                    | AISI304   |
| 7    | Support diffuser       | Stainless steel                    | AISI304   |
| 8    | Inducer                | Stainless steel                    | AISI304   |
| 9    | Inlet & outlet chamber | Cast iron                          | ASTM25B   |
| 11   | Bearing                | Tungsten carbide                   |           |
| 12   | Impeller               | Stainless steel                    | AISI304   |
| 13   | Shaft                  | Stainless steel                    | AISI304   |
| 14   | Impeller sleeve        | Stainless steel                    | AISI304   |
| 15   | Cylinder               | Stainless steel                    | AISI304   |
| 16   | Coupling               | Carbon steel/<br>Powder metallurgy |           |

Please check with us for other materials.


### CDMF 1,3,5 Material list

| Pos. | Name                   | Material                           | AISI/ASTM |
|------|------------------------|------------------------------------|-----------|
| 1    | Motor                  |                                    |           |
| 2    | Pump head              | Cast iron                          | ASTM25B   |
| 3    | Lining                 | Stainless steel                    | AISI304   |
| 4    | Mechanical seal        | Tungsten carbide/<br>Carbon        |           |
| 5    | Top diffuser           | Stainless steel                    | AISI304   |
| 6    | Diffuser               | Stainless steel                    | AISI304   |
| 7    | Support diffuser       | Stainless steel                    | AISI304   |
| 8    | Inducer                | Stainless steel                    | AISI304   |
| 9    | Inlet & outlet chamber | Stainless steel                    | AISI304   |
| 10   | Base plate             | Cast aluminum                      |           |
| 11   | Bearing                | Tungsten carbide                   |           |
| 12   | Impeller               | Stainless steel                    | AISI304   |
| 13   | Shaft                  | Stainless steel                    | AISI304   |
| 14   | Impeller sleeve        | Stainless steel                    | AISI304   |
| 15   | Cylinder               | Stainless steel                    | AISI304   |
| 16   | Coupling               | Carbon steel/<br>Powder metallurgy |           |

## CDM/CDMF 10,15,20 Sectional drawing



CDM



CDMF

### CDM 10,15,20 Material list


| Pos. | Name                      | Material                           | AISI/ASTM |
|------|---------------------------|------------------------------------|-----------|
| 1    | Motor                     |                                    |           |
| 2    | Pump head                 | Cast iron                          | ASTM25B   |
| 4    | Mechanical seal           | Tungsten carbide/<br>Carbon        |           |
| 5    | Top diffuser              | Stainless steel                    | AISI304   |
| 6    | Diffuser                  | Stainless steel                    | AISI304   |
| 7    | Support diffuser          | Stainless steel                    | AISI304   |
| 8    | Inducer                   | Stainless steel                    | AISI304   |
| 9    | Inlet & outlet<br>chamber | Cast iron                          | ASTM25B   |
| 11   | Bearing                   | Tungsten carbide                   |           |
| 12   | Impeller                  | Stainless steel                    | AISI304   |
| 13   | Shaft                     | Stainless steel                    | AISI304   |
| 14   | Impeller sleeve           | Stainless steel                    | AISI304   |
| 15   | Cylinder                  | Stainless steel                    | AISI304   |
| 16   | Coupling                  | Carbon steel/<br>Powder metallurgy |           |

Please check with us for other materials.

### CDMF 10,15,20 Material list

| Pos. | Name                      | Material                           | AISI/ASTM |
|------|---------------------------|------------------------------------|-----------|
| 1    | Motor                     |                                    |           |
| 2    | Pump head                 | Cast iron                          | ASTM25B   |
| 3    | Lining                    | Stainless steel                    | AISI304   |
| 4    | Mechanical seal           | Tungsten carbide/<br>Carbon        |           |
| 5    | Top diffuser              | Stainless steel                    | AISI304   |
| 6    | Diffuser                  | Stainless steel                    | AISI304   |
| 7    | Support diffuser          | Stainless steel                    | AISI304   |
| 8    | Inducer                   | Stainless steel                    | AISI304   |
| 9    | Inlet & outlet<br>chamber | Stainless steel                    | AISI304   |
| 10   | Base plate                | Cast aluminum                      |           |
| 11   | Bearing                   | Tungsten carbide                   |           |
| 12   | Impeller                  | Stainless steel                    | AISI304   |
| 13   | Shaft                     | Stainless steel                    | AISI304   |
| 14   | Impeller sleeve           | Stainless steel                    | AISI304   |
| 15   | Cylinder                  | Stainless steel                    | AISI304   |
| 16   | Coupling                  | Carbon steel/<br>Powder metallurgy |           |

## CDM/CDMF 32,42,65,85 Sectional drawing




CDM

### CDM 32,42,65,85 Material list

| Pos. | Name                   | Material                           | AISI/ASTM |
|------|------------------------|------------------------------------|-----------|
| 1    | Motor                  |                                    |           |
| 2    | Bracket                | Cast iron                          | ASTM25B   |
| 3    | Pump head              | Cast iron                          | ASTM25B   |
| 4    | Mechanical seal        | Tungsten carbide/<br>Carbon        |           |
| 5    | Top diffuser           | Stainless steel                    | AISI304   |
| 6    | Diffuser               | Stainless steel                    | AISI304   |
| 7    | Support diffuser       | Stainless steel                    | AISI304   |
| 8    | Inducer                | Stainless steel                    | AISI304   |
| 9    | Inlet & outlet chamber | Stainless steel                    | AISI304   |
| 11   | Bottom bearing         | Tungsten carbide                   |           |
| 12   | Impeller               | Stainless steel                    | AISI304   |
| 13   | Shaft                  | Stainless steel                    | AISI304   |
| 14   | Intermediate bearing   | Tungsten carbide                   |           |
| 15   | Cylinder               | Stainless steel                    | AISI304   |
| 16   | Coupling               | Carbon steel/<br>Powder metallurgy |           |

Please check with us for other materials.




CDMF


### CDMF 32,42,65,85 Material list

| Pos. | Name                   | Material                           | AISI/ASTM |
|------|------------------------|------------------------------------|-----------|
| 1    | Motor                  |                                    |           |
| 2    | Bracket                | Cast iron                          | ASTM25B   |
| 3    | Pump head              | Stainless steel                    | AISI304   |
| 4    | Mechanical seal        | Tungsten carbide/<br>Carbon        |           |
| 5    | Top diffuser           | Stainless steel                    | AISI304   |
| 6    | Diffuser               | Stainless steel                    | AISI304   |
| 7    | Support diffuser       | Stainless steel                    | AISI304   |
| 8    | Inducer                | Stainless steel                    | AISI304   |
| 9    | Inlet & outlet chamber | Stainless steel                    | AISI304   |
| 10   | Base plate             | Cast iron                          | ASTM25B   |
| 11   | Bottom bearing         | Tungsten carbide                   |           |
| 12   | Impeller               | Stainless steel                    | AISI304   |
| 13   | Shaft                  | Stainless steel                    | AISI304   |
| 14   | Intermediate bearing   | Tungsten carbide                   |           |
| 15   | Cylinder               | Stainless steel                    | AISI304   |
| 16   | Coupling               | Carbon steel/<br>Powder metallurgy |           |

## CDM/CDMF 120,150,200 Sectional drawing



CDM



CDMF

### CDM 120,150,200 Material list

| Pos. | Name                      | Material                           | AISI/ASTM |
|------|---------------------------|------------------------------------|-----------|
| 1    | Motor                     |                                    |           |
| 2    | Bracket                   | Cast iron                          | ASTM25B   |
| 3    | Pump head                 | Cast iron                          | ASTM25B   |
| 4    | Mechanical seal           | Tungsten carbide/<br>Carbon        |           |
| 5    | Discharge                 | Stainless steel                    | AISI304   |
| 6    | Diffuser                  | Stainless steel                    | AISI304   |
| 7    | Support diffuser          | Stainless steel                    | AISI304   |
| 8    | Inducer                   | Stainless steel                    | AISI304   |
| 9    | Inlet & outlet<br>chamber | Stainless steel                    | ASTM25B   |
| 10   | Base plate                | Cast iron                          | ASTM25B   |
| 12   | Impeller                  | Stainless steel                    | AISI304   |
| 13   | Shaft                     | Stainless steel                    | AISI304   |
| 14   | bearing                   | Tungsten carbide                   |           |
| 15   | Cylinder                  | Stainless steel                    | AISI304   |
| 16   | Coupling                  | Carbon steel/<br>Powder metallurgy |           |


### CDMF 120,150,200 Material list

| Pos. | Name                      | Material                           | AISI/ASTM |
|------|---------------------------|------------------------------------|-----------|
| 1    | Motor                     |                                    |           |
| 2    | Bracket                   | Cast iron                          | ASTM25B   |
| 3    | Pump head                 | Stainless steel                    | AISI304   |
| 4    | Mechanical seal           | Tungsten carbide/<br>Carbon        |           |
| 5    | Discharge                 | Stainless steel                    | AISI304   |
| 6    | Diffuser                  | Stainless steel                    | AISI304   |
| 7    | Support diffuser          | Stainless steel                    | AISI304   |
| 8    | Inducer                   | Stainless steel                    | AISI304   |
| 9    | Inlet & outlet<br>chamber | Stainless steel                    | AISI304   |
| 10   | Base plate                | Cast iron                          | ASTM25B   |
| 12   | Impeller                  | Stainless steel                    | AISI304   |
| 13   | Shaft                     | Stainless steel                    | AISI304   |
| 14   | bearing                   | Tungsten carbide                   |           |
| 15   | Cylinder                  | Stainless steel                    | AISI304   |
| 16   | Coupling                  | Carbon steel/<br>Powder metallurgy |           |

Please check with us for other materials.

CDM200 series has no NO.10


## CDM/CDMF 1 Performance curve



## CDM/CDMF 1 Performance table

| Model | Motor |      | Q<br>(m³/h) | 0    | 0.5  | 0.7  | 1    | 1.2  | 1.4  | 1.6  | 1.8 | 2    | 2.2  | 2.4  |
|-------|-------|------|-------------|------|------|------|------|------|------|------|-----|------|------|------|
|       | (kW)  | (hp) |             |      |      |      |      |      |      |      |     |      |      |      |
| 1-2   | 0.37  | 0.5  | H<br>(m)    | 11.8 | 11.5 | 11.2 | 10.5 | 10.3 | 9.7  | 9    | 8   | 6.8  | 5.5  | 4    |
| 1-3   | 0.37  | 0.5  |             | 17.5 | 17   | 16.8 | 16   | 15.6 | 14.8 | 13.5 | 12  | 10   | 8.5  | 6    |
| 1-4   | 0.37  | 0.5  |             | 23.5 | 23   | 22.5 | 21.5 | 21   | 19.8 | 18   | 16  | 13.5 | 11   | 8    |
| 1-5   | 0.37  | 0.5  |             | 29   | 28.5 | 28   | 27   | 26   | 24.5 | 22.5 | 20  | 17   | 14   | 10   |
| 1-6   | 0.37  | 0.5  |             | 35   | 34.5 | 34   | 32.5 | 31.5 | 30   | 27   | 24  | 20.5 | 17   | 12.5 |
| 1-7   | 0.37  | 0.5  |             | 41   | 40.5 | 40   | 39   | 37   | 35   | 32   | 28  | 24   | 20   | 15   |
| 1-8   | 0.55  | 0.75 |             | 47   | 46   | 45.5 | 43.5 | 42   | 40   | 37   | 33  | 29   | 24.5 | 18   |
| 1-9   | 0.55  | 0.75 |             | 52.5 | 52   | 51.5 | 49   | 47   | 44.5 | 41   | 37  | 32   | 27   | 20.5 |
| 1-10  | 0.55  | 0.75 |             | 58.5 | 58   | 57   | 55   | 52.5 | 50   | 46   | 42  | 37   | 31   | 23   |
| 1-11  | 0.55  | 0.75 |             | 64   | 63.5 | 63   | 61   | 58.5 | 55   | 51   | 46  | 40   | 33.5 | 25.5 |
| 1-12  | 0.75  | 1    |             | 70   | 69   | 68.5 | 67   | 64.5 | 61   | 57   | 52  | 45.5 | 37   | 28   |
| 1-13  | 0.75  | 1    |             | 75.5 | 75   | 74.5 | 73   | 70   | 66.5 | 61.5 | 56  | 49   | 40.5 | 31   |
| 1-15  | 0.75  | 1    |             | 87.5 | 86.5 | 85.5 | 84   | 81   | 76.5 | 71   | 65  | 57   | 47   | 36   |
| 1-17  | 1.1   | 1.5  |             | 99   | 98   | 97   | 95   | 91.5 | 86.5 | 81   | 73  | 64   | 53   | 41   |
| 1-19  | 1.1   | 1.5  |             | 110  | 109  | 108  | 106  | 103  | 98   | 91   | 82  | 72   | 59   | 46   |
| 1-21  | 1.1   | 1.5  |             | 122  | 121  | 120  | 117  | 113  | 107  | 100  | 90  | 78   | 65   | 50   |
| 1-22  | 1.1   | 1.5  |             | 128  | 127  | 126  | 122  | 118  | 112  | 105  | 95  | 83   | 69   | 54   |
| 1-23  | 1.5   | 2    |             | 134  | 133  | 132  | 128  | 123  | 118  | 111  | 102 | 90.5 | 76.5 | 58   |
| 1-25  | 1.5   | 2    |             | 146  | 145  | 144  | 139  | 134  | 128  | 121  | 111 | 98   | 83   | 63   |
| 1-27  | 1.5   | 2    |             | 158  | 157  | 155  | 150  | 145  | 138  | 130  | 119 | 106  | 90   | 69   |
| 1-30  | 1.5   | 2    |             | 175  | 174  | 172  | 167  | 161  | 154  | 145  | 133 | 118  | 100  | 77   |
| 1-32  | 2.2   | 3    |             | 189  | 188  | 186  | 180  | 174  | 166  | 155  | 143 | 129  | 110  | 85   |
| 1-33  | 2.2   | 3    |             | 195  | 194  | 192  | 186  | 180  | 171  | 160  | 148 | 133  | 113  | 87   |
| 1-34  | 2.2   | 3    |             | 200  | 199  | 198  | 192  | 185  | 176  | 165  | 152 | 137  | 117  | 90   |
| 1-36  | 2.2   | 3    |             | 212  | 211  | 209  | 203  | 196  | 186  | 175  | 161 | 145  | 124  | 95   |
| 1-38  | 2.2   | 3    |             | 225  | 224  | 221  | 215  | 208  | 197  | 185  | 171 | 153  | 131  | 101  |
| 1-40  | 2.2   | 3    |             | 237  | 236  | 233  | 226  | 219  | 208  | 195  | 180 | 161  | 138  | 106  |

## CDM/CDMF 3 Performance curve






## CDM/CDMF 3 Performance table

| Model | Motor |      | Q<br>(m³/h) | 0    | 1.2  | 1.6  | 2    | 2.4  | 2.8  | 3   | 3.2  | 3.6 | 4    | 4.4  |
|-------|-------|------|-------------|------|------|------|------|------|------|-----|------|-----|------|------|
|       | (kW)  | (hp) |             |      |      |      |      |      |      |     |      |     |      |      |
| 3-2   | 0.37  | 0.5  | H<br>(m)    | 14.7 | 14   | 13.5 | 13   | 12.5 | 11.5 | 11  | 10.5 | 9.5 | 8    | 6    |
| 3-3   | 0.37  | 0.5  |             | 22.2 | 21.5 | 21   | 20.5 | 19.5 | 18   | 17  | 16.5 | 15  | 12.5 | 9.5  |
| 3-4   | 0.37  | 0.5  |             | 29.7 | 29   | 28.5 | 27.5 | 26   | 24   | 23  | 22   | 20  | 17   | 13   |
| 3-5   | 0.55  | 0.75 |             | 37.2 | 36   | 35   | 33.5 | 32   | 30   | 29  | 28   | 25  | 21   | 16   |
| 3-6   | 0.55  | 0.75 |             | 45   | 43.5 | 42.5 | 41   | 39   | 36.5 | 35  | 33.5 | 30  | 25   | 19.5 |
| 3-7   | 0.75  | 1    |             | 52.5 | 51   | 50   | 49   | 46   | 43   | 41  | 39.5 | 35  | 30   | 23   |
| 3-8   | 0.75  | 1    |             | 60   | 58.5 | 58   | 56   | 53   | 49   | 47  | 45   | 40  | 34   | 26.5 |
| 3-9   | 1.1   | 1.5  |             | 67.5 | 66   | 65   | 63   | 60   | 56   | 53  | 51   | 45  | 38   | 30   |
| 3-10  | 1.1   | 1.5  |             | 75   | 73   | 72   | 70   | 66   | 61   | 59  | 56   | 50  | 42   | 33.5 |
| 3-11  | 1.1   | 1.5  |             | 82.5 | 80   | 79   | 77   | 73   | 68   | 65  | 62   | 55  | 47   | 37   |
| 3-12  | 1.1   | 1.5  |             | 90   | 88   | 86   | 83   | 79   | 74   | 71  | 67   | 59  | 50   | 40.5 |
| 3-13  | 1.5   | 2    |             | 98   | 95   | 93   | 90   | 86   | 80   | 77  | 73   | 64  | 54   | 44   |
| 3-14  | 1.5   | 2    |             | 105  | 102  | 101  | 98   | 92.5 | 86   | 83  | 78   | 69  | 58   | 47   |
| 3-15  | 1.5   | 2    |             | 113  | 110  | 108  | 105  | 100  | 94   | 90  | 86   | 76  | 64   | 51   |
| 3-16  | 1.5   | 2    |             | 120  | 118  | 116  | 112  | 107  | 100  | 96  | 92   | 81  | 69   | 54   |
| 3-18  | 2.2   | 3    |             | 136  | 133  | 130  | 126  | 120  | 113  | 108 | 102  | 90  | 76   | 61   |
| 3-19  | 2.2   | 3    |             | 143  | 140  | 137  | 132  | 126  | 119  | 114 | 108  | 96  | 82   | 64   |
| 3-20  | 2.2   | 3    |             | 151  | 148  | 144  | 140  | 133  | 125  | 120 | 114  | 100 | 85   | 67   |
| 3-21  | 2.2   | 3    |             | 158  | 155  | 152  | 147  | 140  | 131  | 126 | 120  | 106 | 90   | 71   |
| 3-22  | 2.2   | 3    |             | 166  | 162  | 158  | 154  | 146  | 137  | 132 | 125  | 110 | 93   | 74   |
| 3-23  | 2.2   | 3    |             | 173  | 170  | 166  | 161  | 153  | 144  | 138 | 131  | 115 | 97   | 78   |
| 3-24  | 2.2   | 3    |             | 181  | 177  | 173  | 168  | 160  | 150  | 144 | 137  | 120 | 101  | 81   |
| 3-25  | 3     | 4    |             | 188  | 185  | 181  | 175  | 166  | 156  | 150 | 142  | 125 | 105  | 85   |
| 3-27  | 3     | 4    |             | 204  | 200  | 195  | 188  | 180  | 169  | 162 | 155  | 138 | 117  | 92   |
| 3-28  | 3     | 4    |             | 212  | 207  | 202  | 195  | 187  | 175  | 168 | 160  | 143 | 121  | 95   |
| 3-29  | 3     | 4    |             | 220  | 215  | 210  | 203  | 194  | 182  | 175 | 167  | 148 | 126  | 99   |
| 3-31  | 3     | 4    |             | 235  | 230  | 224  | 216  | 207  | 194  | 187 | 178  | 159 | 134  | 106  |


## CDM/CDMF 5 Performance curve



## CDM/CDMF 5 Performance table

| Model | Motor |      | Q<br>(m³/h) | 0    | 2.5  | 3     | 4    | 5    | 6    | 7    | 8    | 8.5  |
|-------|-------|------|-------------|------|------|-------|------|------|------|------|------|------|
|       | (kW)  | (hp) |             |      |      |       |      |      |      |      |      |      |
| 5-2   | 0.37  | 0.5  | H<br>(m)    | 14.7 | 13.5 | 13.3  | 12.5 | 11.5 | 9    | 7    | 5    | 4    |
| 5-3   | 0.55  | 0.75 |             | 22.1 | 21   | 20.5  | 19   | 17.5 | 15   | 12   | 9    | 7.5  |
| 5-4   | 0.55  | 0.75 |             | 29.5 | 28   | 27.5  | 26   | 24   | 21   | 17   | 13   | 11   |
| 5-5   | 0.75  | 1    |             | 37   | 35   | 34.5  | 33   | 30   | 27   | 23   | 18   | 15   |
| 5-6   | 1.1   | 1.5  |             | 44.5 | 42   | 41.5  | 40   | 37   | 33   | 27   | 21   | 18   |
| 5-7   | 1.1   | 1.5  |             | 52   | 49.5 | 48.5  | 46   | 42.5 | 38.5 | 31.5 | 24.5 | 21   |
| 5-8   | 1.1   | 1.5  |             | 59   | 57   | 56    | 53   | 49   | 44   | 36   | 28   | 24   |
| 5-9   | 1.5   | 2    |             | 67   | 64   | 63    | 60   | 55   | 49.5 | 41.5 | 31.5 | 27   |
| 5-10  | 1.5   | 2    |             | 74.5 | 71   | 70    | 66   | 62   | 55   | 46   | 35   | 30   |
| 5-11  | 1.5   | 2    |             | 82   | 78   | 77    | 73   | 68   | 61   | 51   | 39   | 33   |
| 5-12  | 2.2   | 3    |             | 89.5 | 85   | 84    | 81   | 74.5 | 66   | 55   | 43   | 37   |
| 5-13  | 2.2   | 3    |             | 97   | 92   | 91    | 87   | 80   | 71   | 60   | 47   | 40   |
| 5-14  | 2.2   | 3    |             | 104  | 100  | 98    | 93   | 87   | 77   | 65   | 51   | 43.5 |
| 5-15  | 2.2   | 3    |             | 112  | 107  | 106   | 100  | 93   | 82   | 69   | 54   | 46.5 |
| 5-16  | 2.2   | 3    |             | 119  | 114  | 112   | 107  | 99   | 88   | 74   | 58   | 50   |
| 5-17  | 3     | 4    |             | 127  | 121  | 118.5 | 113  | 105  | 94   | 79   | 62   | 53   |
| 5-18  | 3     | 4    |             | 134  | 128  | 126   | 120  | 111  | 99   | 84   | 66   | 56   |
| 5-20  | 3     | 4    |             | 149  | 143  | 140   | 133  | 124  | 110  | 93   | 73   | 63   |
| 5-21  | 3     | 4    |             | 157  | 150  | 147   | 140  | 130  | 116  | 98   | 77   | 66   |
| 5-22  | 4     | 5.5  |             | 164  | 157  | 154   | 146  | 136  | 122  | 103  | 82   | 70   |
| 5-23  | 4     | 5.5  |             | 172  | 165  | 161   | 153  | 142  | 128  | 108  | 86   | 74   |
| 5-24  | 4     | 5.5  |             | 179  | 172  | 168   | 160  | 149  | 133  | 113  | 90   | 77   |
| 5-25  | 4     | 5.5  |             | 187  | 179  | 175   | 167  | 155  | 139  | 117  | 93   | 80   |
| 5-27  | 4     | 5.5  |             | 202  | 193  | 189   | 180  | 168  | 150  | 127  | 101  | 86   |
| 5-28  | 4     | 5.5  |             | 210  | 201  | 197   | 187  | 174  | 156  | 132  | 105  | 90   |
| 5-29  | 5.5   | 7.5  |             | 217  | 208  | 204   | 194  | 180  | 163  | 139  | 111  | 95   |
| 5-30  | 5.5   | 7.5  |             | 225  | 216  | 212   | 201  | 186  | 169  | 144  | 115  | 98   |
| 5-33  | 5.5   | 7.5  |             | 249  | 238  | 234   | 222  | 206  | 187  | 160  | 127  | 109  |


## CDM/CDMF 10 Performance curve



## CDM/CDMF 10 Performance table

| Model | Motor |      | Q<br>(m³/h) | 0     | 5    | 6    | 8    | 10   | 12   | 14   |
|-------|-------|------|-------------|-------|------|------|------|------|------|------|
|       | (kW)  | (hp) |             |       |      |      |      |      |      |      |
| 10-1  | 0.75  | 1    | H<br>(m)    | 11    | 10.2 | 10   | 9    | 8    | 7    | 4.5  |
| 10-2  | 0.75  | 1    |             | 22.2  | 21   | 20.5 | 19   | 16.5 | 13.5 | 9.5  |
| 10-3  | 1.1   | 1.5  |             | 33.3  | 31.5 | 31   | 28.5 | 25.5 | 22   | 16.5 |
| 10-4  | 1.5   | 2    |             | 44.5  | 42   | 41   | 38   | 34   | 29   | 22   |
| 10-5  | 2.2   | 3    |             | 56    | 52.5 | 51   | 48   | 43   | 37   | 28   |
| 10-6  | 2.2   | 3    |             | 67    | 63   | 62   | 58   | 52   | 44   | 34   |
| 10-7  | 3     | 4    |             | 78.5  | 74   | 73   | 69   | 62   | 52   | 40   |
| 10-8  | 3     | 4    |             | 90    | 85   | 84   | 79   | 71   | 60   | 46   |
| 10-9  | 4     | 5.5  |             | 101.5 | 96   | 94   | 89   | 80   | 67   | 52   |
| 10-10 | 4     | 5.5  |             | 113   | 107  | 105  | 98   | 89   | 76   | 58   |
| 10-11 | 4     | 5.5  |             | 124   | 118  | 115  | 108  | 98   | 84   | 64   |
| 10-12 | 4.5   |      |             | 137   | 129  | 127  | 119  | 107  | 91   | 70   |
| 10-13 | 5.5   | 7.5  |             | 147   | 140  | 138  | 130  | 116  | 99   | 76   |
| 10-14 | 5.5   | 7.5  |             | 160   | 151  | 148  | 139  | 125  | 106  | 82   |
| 10-15 | 5.5   | 7.5  |             | 171   | 162  | 159  | 149  | 134  | 114  | 88   |
| 10-16 | 7.5   | 10   |             | 183   | 173  | 170  | 159  | 144  | 123  | 94   |
| 10-17 | 7.5   | 10   |             | 194   | 184  | 180  | 169  | 153  | 130  | 100  |
| 10-18 | 7.5   | 10   |             | 205   | 195  | 191  | 180  | 163  | 141  | 108  |
| 10-19 | 7.5   | 10   |             | 217   | 206  | 201  | 190  | 172  | 147  | 113  |
| 10-20 | 7.5   | 10   |             | 228   | 217  | 213  | 200  | 181  | 155  | 120  |
| 10-21 | 7.5   | 10   |             | 240   | 228  | 223  | 210  | 191  | 162  | 126  |
| 10-22 | 11    | 15   |             | 250   | 240  | 235  | 221  | 201  | 171  | 132  |

## CDM/CDMF 15 Performance curve




## CDM/CDMF 15 Performance table

| Model | Motor |      | Q<br>(m³/h) | 0    | 8    | 10  | 12   | 14   | 15   | 16   | 18  | 20  | 22   | 24   |
|-------|-------|------|-------------|------|------|-----|------|------|------|------|-----|-----|------|------|
|       | (kW)  | (hp) |             |      |      |     |      |      |      |      |     |     |      |      |
| 15-1  | 1.1   | 1.5  | H<br>(m)    | 12.6 | 12.2 | 12  | 11.8 | 11.5 | 11   | 10.5 | 10  | 9   | 8    | 6.5  |
| 15-2  | 2.2   | 3    |             | 26   | 24.5 | 24  | 23.5 | 23   | 22.5 | 21.5 | 20  | 18  | 16   | 13.5 |
| 15-3  | 3     | 4    |             | 40   | 37.5 | 37  | 36.5 | 35.5 | 34.5 | 34   | 32  | 29  | 25   | 21   |
| 15-4  | 4     | 5.5  |             | 54   | 50.5 | 50  | 49   | 47.5 | 47   | 46   | 43  | 39  | 34   | 28.5 |
| 15-5  | 4     | 5.5  |             | 68   | 63   | 62  | 61   | 59   | 58   | 57   | 53  | 48  | 42.5 | 36   |
| 15-6  | 5.5   | 7.5  |             | 82   | 76   | 75  | 73   | 71   | 69   | 67   | 63  | 58  | 52   | 43   |
| 15-7  | 5.5   | 7.5  |             | 96   | 89   | 88  | 86   | 83   | 81   | 79   | 74  | 68  | 61   | 51   |
| 15-8  | 7.5   | 10   |             | 110  | 102  | 100 | 98   | 95   | 93   | 91   | 85  | 78  | 69   | 59   |
| 15-9  | 7.5   | 10   |             | 124  | 115  | 113 | 111  | 108  | 106  | 103  | 96  | 88  | 78   | 67   |
| 15-10 | 11    | 15   |             | 138  | 128  | 126 | 124  | 121  | 118  | 115  | 107 | 98  | 87   | 75   |
| 15-11 | 11    | 15   |             | 151  | 142  | 140 | 137  | 133  | 130  | 126  | 117 | 107 | 95   | 83   |
| 15-12 | 11    | 15   |             | 166  | 154  | 152 | 149  | 145  | 142  | 138  | 129 | 117 | 104  | 90   |
| 15-13 | 11    | 15   |             | 180  | 167  | 164 | 160  | 155  | 152  | 148  | 138 | 126 | 113  | 99   |
| 15-14 | 11    | 15   |             | 194  | 180  | 177 | 173  | 168  | 165  | 160  | 149 | 136 | 122  | 106  |
| 15-15 | 15    | 20   |             | 208  | 196  | 192 | 188  | 182  | 178  | 173  | 161 | 147 | 132  | 116  |
| 15-16 | 15    | 20   |             | 222  | 209  | 205 | 200  | 194  | 189  | 184  | 172 | 157 | 142  | 125  |
| 15-17 | 15    | 20   |             | 236  | 222  | 218 | 213  | 206  | 201  | 196  | 183 | 167 | 151  | 132  |
| 15-18 | 15    | 20   |             | 250  | 235  | 231 | 225  | 218  | 213  | 207  | 194 | 177 | 160  | 141  |




## CDM/CDMF 20 Performance curve



## CDM/CDMF 20 Performance table

| Model | Motor |      | Q<br>(m³/h) | 0    | 10   | 12   | 14   | 16   | 18  | 20   | 22  | 24  | 26  | 28  | 29   |
|-------|-------|------|-------------|------|------|------|------|------|-----|------|-----|-----|-----|-----|------|
|       | (kW)  | (hp) |             |      |      |      |      |      |     |      |     |     |     |     |      |
| 20-1  | 1.1   | 1.5  | H<br>(m)    | 13.3 | 12.5 | 12.3 | 12   | 11.5 | 11  | 10.5 | 10  | 9.5 | 9   | 8   | 7    |
| 20-2  | 2.2   | 3    |             | 27.2 | 25.5 | 25   | 24.5 | 24   | 23  | 22   | 21  | 20  | 18  | 16  | 14.5 |
| 20-3  | 4     | 5.5  |             | 41.5 | 39.5 | 39   | 38   | 37   | 36  | 34.5 | 33  | 31  | 28  | 25  | 23.5 |
| 20-4  | 5.5   | 7.5  |             | 55.5 | 52.5 | 51   | 50   | 49   | 48  | 46   | 44  | 41  | 37  | 33  | 31.5 |
| 20-5  | 5.5   | 7.5  |             | 69.5 | 66   | 65   | 64   | 62   | 60  | 58   | 55  | 51  | 47  | 42  | 40   |
| 20-6  | 7.5   | 10   |             | 83.8 | 79   | 78   | 77   | 75   | 73  | 70   | 66  | 62  | 58  | 52  | 48   |
| 20-7  | 7.5   | 10   |             | 98   | 92.5 | 91   | 90   | 88   | 85  | 82   | 78  | 73  | 68  | 61  | 57.5 |
| 20-8  | 11    | 15   |             | 113  | 106  | 105  | 103  | 101  | 98  | 95   | 90  | 84  | 77  | 70  | 66   |
| 20-10 | 11    | 15   |             | 141  | 133  | 132  | 130  | 127  | 123 | 119  | 113 | 106 | 97  | 88  | 83   |
| 20-12 | 15    | 20   |             | 171  | 160  | 158  | 156  | 153  | 149 | 143  | 137 | 127 | 117 | 106 | 100  |
| 20-14 | 15    | 20   |             | 201  | 187  | 185  | 183  | 179  | 174 | 168  | 160 | 149 | 137 | 124 | 117  |
| 20-17 | 18.5  | 25   |             | 244  | 228  | 225  | 222  | 218  | 212 | 205  | 195 | 182 | 168 | 154 | 147  |


## CDM/CDMF 32 Performance curve



## CDM/CDMF 32 Performance table

| Model   | Motor |      | Q<br>(m³/h) | 0   | 16  | 20  | 24  | 28  | 32  | 36  | 40  |
|---------|-------|------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|
|         | (kW)  | (hp) |             |     |     |     |     |     |     |     |     |
| 32-1-1  | 1.5   | 2    | H<br>(m)    | 15  | 14  | 13  | 12  | 11  | 9   | 7   | 4   |
| 32-1    | 2.2   | 3    |             | 20  | 18  | 17  | 15  | 14  | 13  | 11  | 8   |
| 32-2-2  | 3     | 4    |             | 33  | 29  | 28  | 26  | 23  | 20  | 16  | 11  |
| 32-2    | 4     | 5.5  |             | 40  | 36  | 34  | 32  | 29  | 27  | 23  | 18  |
| 32-3-2  | 5.5   | 7.5  |             | 50  | 47  | 44  | 41  | 38  | 33  | 28  | 21  |
| 32-3    | 5.5   | 7.5  |             | 57  | 54  | 51  | 48  | 44  | 40  | 35  | 27  |
| 32-4-2  | 7.5   | 10   |             | 72  | 65  | 62  | 58  | 53  | 46  | 40  | 30  |
| 32-4    | 7.5   | 10   |             | 78  | 72  | 69  | 65  | 59  | 53  | 47  | 37  |
| 32-5-2  | 11    | 15   |             | 92  | 83  | 79  | 74  | 68  | 60  | 52  | 41  |
| 32-5    | 11    | 15   |             | 99  | 90  | 86  | 81  | 74  | 67  | 59  | 47  |
| 32-6-2  | 11    | 15   |             | 108 | 101 | 97  | 90  | 83  | 74  | 65  | 51  |
| 32-6    | 11    | 15   |             | 118 | 108 | 104 | 97  | 90  | 81  | 72  | 57  |
| 32-7-2  | 15    | 20   |             | 129 | 119 | 114 | 107 | 98  | 88  | 78  | 60  |
| 32-7    | 15    | 20   |             | 138 | 126 | 121 | 113 | 105 | 95  | 85  | 67  |
| 32-8-2  | 15    | 20   |             | 145 | 136 | 131 | 123 | 114 | 102 | 90  | 71  |
| 32-8    | 15    | 20   |             | 154 | 144 | 138 | 130 | 120 | 109 | 97  | 77  |
| 32-9-2  | 18.5  | 25   |             | 163 | 154 | 148 | 140 | 129 | 117 | 102 | 80  |
| 32-9    | 18.5  | 25   |             | 172 | 162 | 156 | 147 | 136 | 124 | 109 | 88  |
| 32-10-2 | 18.5  | 25   |             | 182 | 175 | 166 | 157 | 146 | 131 | 115 | 91  |
| 32-10   | 18.5  | 25   |             | 193 | 182 | 173 | 164 | 152 | 138 | 122 | 98  |
| 32-11-2 | 22    | 30   |             | 204 | 193 | 184 | 173 | 164 | 146 | 128 | 102 |
| 32-11   | 22    | 30   |             | 210 | 200 | 191 | 180 | 168 | 153 | 135 | 109 |
| 32-12-2 | 22    | 30   |             | 222 | 211 | 201 | 189 | 178 | 160 | 140 | 113 |
| 32-12   | 22    | 30   |             | 231 | 218 | 208 | 196 | 184 | 167 | 147 | 120 |
| 32-13-2 | 30    | 40   |             | 246 | 230 | 218 | 206 | 193 | 174 | 153 | 124 |
| 32-13   | 30    | 40   |             | 253 | 237 | 225 | 213 | 200 | 181 | 160 | 131 |
| 32-14-2 | 30    | 40   |             | 265 | 247 | 235 | 222 | 210 | 189 | 165 | 135 |
| 32-14   | 30    | 40   |             | 273 | 255 | 242 | 229 | 216 | 196 | 172 | 142 |
| 32-15-2 | 30    | 40   |             | 284 | 266 | 253 | 239 | 224 | 203 | 178 | 145 |
| 32-15   | 30    | 40   |             | 292 | 274 | 260 | 246 | 231 | 210 | 185 | 152 |
| 32-16-2 | 30    | 40   |             | 304 | 284 | 270 | 255 | 240 | 218 | 190 | 156 |
| 32-16   | 30    | 40   |             | 312 | 292 | 277 | 262 | 246 | 225 | 197 | 163 |


## CDM/CDMF 42 Performance curve



## CDM/CDMF 42 Performance table

| Model   | Motor |      | Q<br>(m³/h) | 0   | 25  | 30  | 35  | 40  | 42  | 45  | 50  | 55  |
|---------|-------|------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|
|         | (kW)  | (hp) |             |     |     |     |     |     |     |     |     |     |
| 42-1-1  | 3.0   | 4    | H<br>(m)    | 20  | 20  | 19  | 18  | 17  | 16  | 15  | 13  | 11  |
| 42-1    | 4.0   | 5.5  |             | 27  | 24  | 23  | 22  | 21  | 20  | 19  | 18  | 16  |
| 42-2-2  | 5.5   | 7.5  |             | 42  | 40  | 38  | 36  | 33  | 32  | 30  | 27  | 23  |
| 42-2    | 7.5   | 10   |             | 50  | 48  | 46  | 44  | 42  | 41  | 39  | 35  | 31  |
| 42-3-2  | 11    | 15   |             | 66  | 63  | 61  | 58  | 54  | 52  | 50  | 44  | 38  |
| 42-3    | 11    | 15   |             | 75  | 71  | 69  | 66  | 63  | 61  | 58  | 53  | 47  |
| 42-4-2  | 15    | 20   |             | 92  | 87  | 84  | 80  | 75  | 73  | 69  | 62  | 54  |
| 42-4    | 15    | 20   |             | 100 | 95  | 92  | 88  | 84  | 81  | 78  | 71  | 62  |
| 42-5-2  | 18.5  | 25   |             | 118 | 111 | 107 | 102 | 96  | 93  | 88  | 80  | 69  |
| 42-5    | 18.5  | 25   |             | 125 | 119 | 115 | 110 | 105 | 101 | 97  | 88  | 78  |
| 42-6-2  | 22    | 30   |             | 142 | 135 | 130 | 124 | 117 | 113 | 108 | 97  | 85  |
| 42-6    | 22    | 30   |             | 150 | 143 | 138 | 132 | 125 | 122 | 116 | 106 | 93  |
| 42-7-2  | 30    | 40   |             | 166 | 158 | 152 | 146 | 138 | 134 | 127 | 115 | 100 |
| 42-7    | 30    | 40   |             | 175 | 166 | 161 | 154 | 146 | 142 | 135 | 124 | 109 |
| 42-8-2  | 30    | 40   |             | 192 | 182 | 175 | 168 | 159 | 154 | 146 | 133 | 116 |
| 42-8    | 30    | 40   |             | 202 | 190 | 184 | 176 | 167 | 162 | 154 | 141 | 124 |
| 42-9-2  | 30    | 40   |             | 212 | 205 | 198 | 190 | 180 | 174 | 166 | 150 | 132 |
| 42-9    | 37    | 50   |             | 220 | 214 | 207 | 198 | 188 | 183 | 174 | 159 | 140 |
| 42-10-2 | 37    | 50   |             | 237 | 230 | 221 | 212 | 200 | 194 | 185 | 168 | 147 |
| 42-10   | 37    | 50   |             | 245 | 238 | 230 | 220 | 209 | 203 | 193 | 177 | 155 |
| 42-11-2 | 45    | 60   |             | 262 | 255 | 246 | 236 | 223 | 217 | 206 | 188 | 165 |
| 42-11   | 45    | 60   |             | 269 | 263 | 255 | 244 | 232 | 225 | 214 | 196 | 173 |
| 42-12-2 | 45    | 60   |             | 284 | 280 | 270 | 259 | 245 | 238 | 226 | 206 | 181 |
| 42-12   | 45    | 60   |             | 290 | 289 | 280 | 268 | 255 | 247 | 236 | 216 | 190 |
| 42-13-2 | 45    | 60   |             | 312 | 305 | 294 | 282 | 267 | 259 | 247 | 225 | 198 |

## CDM/CDMF 65 Performance curve




## CDM/CDMF 65 Performance table

| Model  | Motor |      | Q<br>(m³/h) | 0   | 30  | 40  | 50  | 60  | 65  | 70  | 80  |
|--------|-------|------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|
|        | (kW)  | (hp) |             |     |     |     |     |     |     |     |     |
| 65-1-1 | 4     | 5.5  | H<br>(m)    | 20  | 19  | 18  | 16  | 14  | 13  | 11  | 8   |
| 65-1   | 5.5   | 7.5  |             | 30  | 27  | 25  | 23  | 21  | 20  | 18  | 15  |
| 65-2-2 | 7.5   | 10   |             | 42  | 39  | 36  | 33  | 29  | 26  | 23  | 17  |
| 65-2-1 | 11    | 15   |             | 50  | 46  | 44  | 40  | 36  | 33  | 30  | 24  |
| 65-2   | 11    | 15   |             | 60  | 53  | 51  | 47  | 43  | 40  | 37  | 30  |
| 65-3-2 | 15    | 20   |             | 73  | 66  | 62  | 56  | 50  | 46  | 41  | 32  |
| 65-3-1 | 15    | 20   |             | 80  | 73  | 69  | 63  | 57  | 53  | 48  | 39  |
| 65-3   | 18.5  | 25   |             | 87  | 80  | 76  | 70  | 64  | 60  | 55  | 46  |
| 65-4-2 | 18.5  | 25   |             | 98  | 92  | 87  | 80  | 71  | 66  | 60  | 47  |
| 65-4-1 | 22    | 30   |             | 107 | 100 | 94  | 87  | 78  | 73  | 67  | 54  |
| 65-4   | 22    | 30   |             | 116 | 107 | 101 | 94  | 85  | 80  | 74  | 61  |
| 65-5-2 | 30    | 40   |             | 130 | 121 | 114 | 105 | 95  | 88  | 80  | 64  |
| 65-5-1 | 30    | 40   |             | 138 | 128 | 121 | 112 | 102 | 95  | 87  | 71  |
| 65-5   | 30    | 40   |             | 146 | 136 | 129 | 119 | 109 | 102 | 94  | 78  |
| 65-6-2 | 30    | 40   |             | 158 | 150 | 142 | 131 | 118 | 110 | 101 | 81  |
| 65-6-1 | 37    | 50   |             | 166 | 157 | 149 | 138 | 125 | 117 | 108 | 88  |
| 65-6   | 37    | 50   |             | 175 | 164 | 156 | 145 | 132 | 124 | 115 | 95  |
| 65-7-2 | 37    | 50   |             | 186 | 179 | 169 | 156 | 141 | 132 | 121 | 99  |
| 65-7-1 | 37    | 50   |             | 196 | 186 | 176 | 163 | 148 | 139 | 128 | 106 |
| 65-7   | 45    | 60   |             | 205 | 193 | 183 | 170 | 155 | 146 | 135 | 112 |
| 65-8-2 | 45    | 60   |             | 216 | 207 | 196 | 182 | 164 | 154 | 142 | 116 |
| 65-8-1 | 45    | 60   |             | 225 | 215 | 203 | 189 | 171 | 161 | 149 | 123 |




## CDM/CDMF 85 Performance curve



## CDM/CDMF 85 Performance table

| Model  | Motor |      | Q<br>(m³/h) | 0   | 50  | 60  | 70  | 80  | 85  | 90  | 100 | 110 |
|--------|-------|------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|
|        | (kW)  | (hp) |             |     |     |     |     |     |     |     |     |     |
| 85-1-1 | 5.5   | 7.5  | H<br>(m)    | 26  | 22  | 19  | 17  | 16  | 14  | 13  | 10  | 6   |
| 85-1   | 7.5   | 10   |             | 33  | 25  | 24  | 22  | 21  | 20  | 19  | 16  | 12  |
| 85-2-2 | 11    | 15   |             | 47  | 41  | 39  | 36  | 32  | 30  | 28  | 22  | 15  |
| 85-2   | 15    | 20   |             | 67  | 53  | 50  | 47  | 44  | 41  | 40  | 36  | 30  |
| 85-3-2 | 18.5  | 25   |             | 75  | 68  | 65  | 60  | 55  | 52  | 49  | 41  | 32  |
| 85-3   | 22    | 30   |             | 98  | 81  | 77  | 72  | 67  | 64  | 62  | 55  | 48  |
| 85-4-2 | 30    | 40   |             | 115 | 98  | 93  | 87  | 80  | 75  | 72  | 62  | 50  |
| 85-4   | 30    | 40   |             | 134 | 110 | 105 | 100 | 92  | 86  | 84  | 76  | 66  |
| 85-5-2 | 37    | 50   |             | 150 | 126 | 120 | 113 | 104 | 98  | 93  | 81  | 68  |
| 85-5   | 37    | 50   |             | 164 | 139 | 131 | 124 | 115 | 110 | 106 | 94  | 83  |
| 85-6-2 | 45    | 60   |             | 177 | 155 | 148 | 139 | 129 | 122 | 117 | 102 | 86  |
| 85-6   | 45    | 60   |             | 197 | 168 | 160 | 150 | 141 | 134 | 130 | 117 | 103 |


## CDM/CDMF 120 Performance curve



## CDM/CDMF 120 Performance table

| Model   | Motor |      | Q<br>(m³/h) | 0    | 60    | 70    | 80    | 90    | 100   | 110   | 120   | 130   | 140   | 150   |
|---------|-------|------|-------------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|         | (kW)  | (hp) |             |      |       |       |       |       |       |       |       |       |       |       |
| 120-1   | 11    | 15   | H<br>(m)    | 23   | 22    | 21.8  | 21.6  | 21    | 20.5  | 19.5  | 18.5  | 17    | 16    | 15    |
| 120-2-2 | 15    | 20   |             | 37   | 34    | 33.6  | 33    | 31    | 30.2  | 30    | 28.5  | 27    | 25    | 24    |
| 120-2-1 | 18.5  | 25   |             | 43   | 41    | 40    | 39.5  | 38.5  | 37    | 36.5  | 34.5  | 32.5  | 30    | 27.5  |
| 120-2   | 22    | 30   |             | 48   | 46    | 45    | 44.5  | 43.5  | 42.4  | 41    | 40    | 38    | 36    | 33.5  |
| 120-3-2 | 30    | 40   |             | 59.5 | 57    | 56    | 55    | 53.5  | 52    | 51    | 49    | 46.5  | 43.5  | 41    |
| 120-3-1 | 30    | 40   |             | 65.5 | 64    | 63    | 62    | 60    | 58.5  | 57.5  | 55.5  | 52    | 49    | 46    |
| 120-3   | 30    | 40   |             | 71   | 69.5  | 68.5  | 67.5  | 66    | 64.4  | 62.5  | 61    | 57.5  | 54.5  | 51    |
| 120-4-2 | 37    | 50   |             | 82   | 80.5  | 79    | 78    | 76    | 73.5  | 72    | 69    | 66    | 61.5  | 58    |
| 120-4-1 | 37    | 50   |             | 91   | 87    | 86    | 84.5  | 82    | 80    | 78    | 76    | 72    | 68    | 64.5  |
| 120-4   | 45    | 60   |             | 96   | 92.5  | 91    | 90    | 88    | 85.5  | 83    | 81    | 77    | 73    | 68.5  |
| 120-5-2 | 45    | 60   |             | 108  | 104.5 | 103   | 101   | 99    | 96    | 93    | 90    | 85.5  | 80.5  | 75.5  |
| 120-5-1 | 45    | 60   |             | 115  | 110.5 | 109   | 107.5 | 105   | 102   | 100   | 97    | 92    | 86.5  | 83    |
| 120-5   | 55    | 75   |             | 121  | 115.5 | 114   | 113   | 110   | 107.5 | 104.5 | 101.5 | 96    | 91    | 86    |
| 120-6-2 | 55    | 75   |             | 131  | 128   | 125.5 | 123   | 121   | 117.3 | 113.5 | 110   | 104.5 | 98.5  | 92.5  |
| 120-6-1 | 55    | 75   |             | 139  | 134   | 132   | 130.5 | 127   | 124   | 121   | 118   | 111   | 105   | 100   |
| 120-6   | 75    | 100  |             | 144  | 139   | 137   | 135   | 132   | 128.8 | 126   | 123   | 116   | 110   | 104   |
| 120-7-2 | 75    | 100  |             | 154  | 151   | 148   | 145.5 | 143   | 138.6 | 134   | 130   | 123.5 | 116.5 | 109   |
| 120-7-1 | 75    | 100  |             | 161  | 156.5 | 154   | 152   | 148.5 | 144.5 | 141   | 137.5 | 130   | 123   | 116.5 |
| 120-7   | 75    | 100  |             | 166  | 162.5 | 160.5 | 158.5 | 155   | 151   | 148   | 145   | 137   | 129   | 123   |


## CDM/CDMF 150 Performance curve



## CDM/CDMF 150 Performance table

| Model   | Motor |      | Q<br>(m³/h) | 0     | 80    | 90    | 100   | 110   | 120   | 130   | 14    | 150   | 160   | 170   | 180  |
|---------|-------|------|-------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|
|         | (kW)  | (hp) |             |       |       |       |       |       |       |       |       |       |       |       |      |
| 150-1-1 | 11    | 15   | H<br>(m)    | 19.5  | 18.3  | 17.8  | 17.3  | 17    | 16    | 15    | 14    | 12.5  | 11    | 10    | 8.5  |
| 150-1   | 15    | 20   |             | 25    | 24    | 23    | 22.5  | 22    | 21.5  | 20.5  | 20    | 18.5  | 17    | 16    | 15   |
| 150-2-2 | 18.5  | 25   |             | 40    | 37    | 35.5  | 34    | 33    | 32    | 31    | 29    | 27.5  | 26    | 23    | 21   |
| 150-2-1 | 22    | 30   |             | 47.5  | 44.3  | 43    | 42    | 40    | 39    | 38.5  | 37.5  | 35    | 33    | 30    | 27   |
| 150-2   | 30    | 40   |             | 55    | 50    | 49    | 48    | 47    | 45.5  | 44    | 42    | 40    | 37    | 34    | 32   |
| 150-3-2 | 30    | 40   |             | 69    | 53.5  | 61    | 59    | 57.5  | 56    | 54.5  | 53    | 49    | 45.5  | 42    | 39   |
| 150-3-1 | 37    | 50   |             | 75    | 70    | 68    | 67    | 65    | 63    | 62    | 60    | 56    | 53    | 49    | 45   |
| 150-3   | 37    | 50   |             | 83    | 78    | 76.5  | 75    | 73    | 70.5  | 68    | 66    | 63    | 59    | 55    | 50.5 |
| 150-4-2 | 45    | 60   |             | 95    | 89    | 87    | 84    | 81.5  | 79    | 77    | 74.5  | 70.5  | 65.5  | 60    | 56   |
| 150-4-1 | 45    | 60   |             | 104   | 96.5  | 94    | 91.5  | 89    | 86.5  | 84    | 81.5  | 77    | 72.5  | 67    | 62   |
| 150-4   | 55    | 75   |             | 112   | 104   | 102   | 100   | 97    | 95    | 91    | 88    | 84    | 79.5  | 74    | 68   |
| 150-5-2 | 55    | 75   |             | 125.5 | 115.5 | 112   | 109   | 106   | 102.5 | 100   | 97    | 92    | 86    | 79    | 73.5 |
| 150-5-1 | 75    | 100  |             | 132   | 122.5 | 119.5 | 117   | 113.5 | 111.5 | 107.5 | 104.5 | 99    | 93.5  | 87    | 80   |
| 150-5   | 75    | 100  |             | 140   | 130   | 127.5 | 125   | 121   | 119   | 115   | 111.5 | 106.5 | 101   | 84.5  | 86.5 |
| 150-6-2 | 75    | 100  |             | 149   | 140   | 137   | 133   | 130   | 126   | 121   | 118   | 112   | 106   | 98    | 81   |
| 150-6-1 | 75    | 100  |             | 158   | 148.5 | 145   | 141.7 | 137.5 | 135   | 131   | 127   | 120.5 | 114.5 | 106.5 | 97.5 |
| 150-6   | 75    | 100  |             | 168   | 157   | 153   | 149   | 145   | 142   | 139.5 | 137   | 130   | 123.5 | 116   | 109  |

## CDM/CDMF 200 Performance curve





## CDM/CDMF 200 Performance table

| Model     | Motor |      | Q<br>(m³/h) | 0     | 100   | 120   | 140   | 160   | 180   | 200 | 220   | 240   |
|-----------|-------|------|-------------|-------|-------|-------|-------|-------|-------|-----|-------|-------|
|           | (kW)  | (hp) |             |       |       |       |       |       |       |     |       |       |
| 200-1-B   | 18.5  | 25   | H<br>(m)    | 28    | 25.5  | 25    | 24    | 23    | 21.5  | 20  | 18    | 15.5  |
| 200-1-A   | 22    | 30   |             | 31    | 29    | 28.5  | 27.5  | 26.5  | 25.5  | 24  | 22    | 20    |
| 200-1     | 30    | 40   |             | 40.5  | 38.5  | 38    | 37.5  | 36.5  | 35    | 34  | 32.5  | 30    |
| 200-2-2B  | 37    | 50   |             | 57    | 53    | 51    | 49    | 47    | 44    | 41  | 37    | 32    |
| 200-2-2A  | 45    | 60   |             | 63    | 59.5  | 58    | 56    | 54    | 52.5  | 49  | 44.5  | 40.5  |
| 200-2-A   | 55    | 75   |             | 73    | 69    | 68    | 66    | 64    | 62    | 59  | 55.5  | 51    |
| 200-2     | 55    | 75   |             | 82.5  | 78.5  | 77.5  | 76    | 74    | 71.5  | 69  | 66    | 61.5  |
| 200-3-2B  | 75    | 100  |             | 98    | 91.5  | 89    | 86.5  | 83.5  | 79    | 75  | 70    | 63    |
| 200-3-A-B | 75    | 100  |             | 100.5 | 95    | 93    | 90    | 87    | 83.5  | 79  | 73.5  | 67    |
| 200-3-2A  | 75    | 100  |             | 106   | 99.5  | 97.5  | 94.5  | 91.5  | 89    | 84  | 78.5  | 72    |
| 200-3-B   | 75    | 100  |             | 111   | 104.5 | 102.5 | 100   | 97    | 93    | 89  | 84.5  | 77.5  |
| 200-3-A   | 75    | 100  |             | 114   | 108   | 106   | 103.5 | 100.5 | 97.5  | 93  | 88    | 81.5  |
| 200-3     | 90    | 120  |             | 123   | 117.5 | 116   | 113.5 | 110.5 | 107   | 103 | 99    | 92    |
| 200-4-2B  | 90    | 120  |             | 139.5 | 131.5 | 129   | 125.5 | 121   | 115.5 | 110 | 103.5 | 94    |
| 200-4-2A  | 110   | 150  |             | 147   | 138.5 | 136   | 132   | 128   | 124   | 118 | 111   | 102.5 |
| 200-4-A   | 110   | 150  |             | 157   | 148   | 145.5 | 142.5 | 138   | 134   | 128 | 122   | 113   |
| 200-4     | 110   | 150  |             | 166   | 157.5 | 155.5 | 152.5 | 148   | 143.5 | 138 | 132.5 | 123.5 |



## CDM/CDMF 1 Installation sketch







Note1: CDM/CDMF1-27~1-40 have no oval flange pipeline connection.  
 Note2: The overall dimensions of the single-phase motor and explosive-proof motor are a little different. Please contact us for details.

## Dimensions and weights

| Model | Dimension (mm) |     |                |     |     | Weight(kg) |      |
|-------|----------------|-----|----------------|-----|-----|------------|------|
|       | H1             | H2  | H(Flange/Oth.) | D1  | D2  | CDM        | CDMF |
| 1-2   | 187            | 215 | 477/452        | 148 | 117 | 23         | 19   |
| 1-3   | 207            | 215 | 497/472        | 148 | 117 | 23         | 19   |
| 1-4   | 227            | 215 | 517/492        | 148 | 117 | 24         | 20   |
| 1-5   | 247            | 215 | 537/512        | 148 | 117 | 24         | 20   |
| 1-6   | 267            | 215 | 557/532        | 148 | 117 | 25         | 21   |
| 1-7   | 287            | 215 | 577/552        | 148 | 117 | 25         | 21   |
| 1-8   | 307            | 215 | 597/572        | 148 | 117 | 27         | 23   |
| 1-9   | 327            | 215 | 617/592        | 148 | 117 | 27         | 23   |
| 1-10  | 347            | 215 | 637/612        | 148 | 117 | 28         | 24   |
| 1-11  | 367            | 215 | 657/632        | 148 | 117 | 28         | 24   |
| 1-12  | 397            | 245 | 717/692        | 170 | 142 | 31         | 27   |
| 1-13  | 417            | 245 | 737/712        | 170 | 142 | 31         | 27   |
| 1-15  | 457            | 245 | 777/752        | 170 | 142 | 32         | 28   |
| 1-17  | 497            | 245 | 817/792        | 170 | 142 | 35         | 31   |
| 1-19  | 537            | 245 | 857/832        | 170 | 142 | 36         | 32   |
| 1-21  | 577            | 245 | 897/872        | 170 | 142 | 36         | 32   |
| 1-22  | 597            | 245 | 917/892        | 170 | 142 | 37         | 33   |
| 1-23  | 617            | 290 | 937/912        | 190 | 155 | 43         | 39   |
| 1-25  | 667            | 290 | 1032/1007      | 190 | 155 | 44         | 40   |
| 1-27  | 707            | 290 | 1072/1047      | 190 | 155 | 45         | 41   |
| 1-30  | 767            | 290 | 1132/1107      | 190 | 155 | 46         | 42   |
| 1-32  | 807            | 290 | 1172/1147      | 190 | 155 | 49         | 45   |
| 1-33  | 827            | 290 | 1192/1167      | 190 | 155 | 49         | 45   |
| 1-34  | 847            | 290 | 1212/1187      | 190 | 155 | 50         | 46   |
| 1-36  | 887            | 290 | 1252/1227      | 190 | 155 | 51         | 47   |
| 1-38  | 927            | 290 | 1292/1267      | 190 | 155 | 51         | 47   |
| 1-40  | 967            | 290 | 1332/1307      | 190 | 155 | 52         | 48   |

## CDM/CDMF 3 Installation sketch








Note1: CDM/CDMF3-21~3-31 have no oval flange pipeline connection.  
 Note2: The overall dimensions of the single-phase motor and explosive-proof motor are a little different. Please contact us for details.

## Dimensions and weights

| Model | Dimension (mm) |     |                |     |     | Weight(kg) |      |
|-------|----------------|-----|----------------|-----|-----|------------|------|
|       | H1             | H2  | H(Flange/Oth.) | D1  | D2  | CDM        | CDMF |
| 3-2   | 187            | 215 | 477/452        | 148 | 117 | 24         | 20   |
| 3-3   | 207            | 215 | 497/472        | 148 | 117 | 24         | 20   |
| 3-4   | 227            | 215 | 517/492        | 148 | 117 | 25         | 21   |
| 3-5   | 247            | 215 | 537/512        | 148 | 117 | 26         | 22   |
| 3-6   | 267            | 215 | 557/532        | 148 | 117 | 27         | 23   |
| 3-7   | 297            | 245 | 617/592        | 170 | 142 | 30         | 26   |
| 3-8   | 317            | 245 | 637/612        | 170 | 142 | 30         | 26   |
| 3-9   | 337            | 245 | 657/632        | 170 | 142 | 32         | 28   |
| 3-10  | 357            | 245 | 677/652        | 170 | 142 | 33         | 29   |
| 3-11  | 377            | 245 | 697/672        | 170 | 142 | 33         | 29   |
| 3-12  | 397            | 245 | 717/692        | 170 | 142 | 34         | 30   |
| 3-13  | 427            | 290 | 792/767        | 190 | 155 | 39         | 35   |
| 3-14  | 447            | 290 | 812/787        | 190 | 155 | 40         | 36   |
| 3-15  | 467            | 290 | 832/807        | 190 | 155 | 40         | 36   |
| 3-16  | 487            | 290 | 852/827        | 190 | 155 | 41         | 37   |
| 3-18  | 527            | 290 | 892/867        | 190 | 155 | 43         | 39   |
| 3-19  | 547            | 290 | 912/887        | 190 | 155 | 44         | 40   |
| 3-20  | 567            | 290 | 932/907        | 190 | 155 | 44         | 40   |
| 3-21  | 587            | 290 | 952/927        | 190 | 155 | 45         | 41   |
| 3-22  | 607            | 290 | 972/947        | 190 | 155 | 45         | 41   |
| 3-23  | 627            | 290 | 992/967        | 190 | 155 | 46         | 42   |
| 3-24  | 647            | 290 | 1012/987       | 190 | 155 | 46         | 42   |
| 3-25  | 677            | 345 | 1097/1072      | 197 | 165 | 57         | 53   |
| 3-27  | 717            | 345 | 1137/1112      | 197 | 165 | 58         | 54   |
| 3-28  | 737            | 345 | 1157/1132      | 197 | 165 | 58         | 54   |
| 3-29  | 757            | 345 | 1177/1152      | 197 | 165 | 58         | 54   |
| 3-31  | 797            | 345 | 1217/1192      | 197 | 165 | 59         | 55   |

## CDM/CDMF 5 Installation sketch





Note1: CDM/CDMF5-21~5-33 have no oval flange pipeline connection.  
 Note2: The overall dimensions of the single-phase motor and explosive-proof motor are a little different. Please contact us for details.

## Dimensions and weights

| Model | Dimension (mm) |     |                |     |     | Weight(kg) |      |
|-------|----------------|-----|----------------|-----|-----|------------|------|
|       | H1             | H2  | H(Flange/Oth.) | D1  | D2  | CDM        | CDMF |
| 5-2   | 201            | 215 | 491/466        | 148 | 117 | 24         | 19   |
| 5-3   | 228            | 215 | 518/493        | 148 | 117 | 26         | 21   |
| 5-4   | 255            | 215 | 545/520        | 148 | 117 | 27         | 22   |
| 5-5   | 292            | 245 | 612/587        | 170 | 142 | 30         | 25   |
| 5-6   | 319            | 245 | 639/614        | 170 | 142 | 32         | 27   |
| 5-7   | 346            | 245 | 666/641        | 170 | 142 | 32         | 27   |
| 5-8   | 373            | 245 | 693/668        | 170 | 142 | 33         | 28   |
| 5-9   | 410            | 290 | 775/750        | 190 | 155 | 38         | 33   |
| 5-10  | 437            | 290 | 802/777        | 190 | 155 | 39         | 34   |
| 5-11  | 464            | 290 | 829/804        | 190 | 155 | 39         | 34   |
| 5-12  | 491            | 290 | 856/831        | 190 | 155 | 42         | 37   |
| 5-13  | 518            | 290 | 883/858        | 190 | 155 | 42         | 37   |
| 5-14  | 545            | 290 | 910/885        | 190 | 155 | 43         | 38   |
| 5-15  | 572            | 290 | 937/912        | 190 | 155 | 43         | 38   |
| 5-16  | 599            | 290 | 964/939        | 190 | 155 | 44         | 39   |
| 5-17  | 636            | 345 | 1056/1030      | 197 | 165 | 55         | 50   |
| 5-18  | 663            | 345 | 1083/1058      | 197 | 165 | 55         | 50   |
| 5-20  | 717            | 345 | 1137/1112      | 197 | 165 | 56         | 51   |
| 5-21  | 744            | 345 | 1164/1139      | 197 | 165 | 57         | 52   |
| 5-22  | 771            | 355 | 1201/1176      | 230 | 188 | 64         | 59   |
| 5-23  | 798            | 355 | 1228/1203      | 230 | 188 | 65         | 60   |
| 5-24  | 825            | 355 | 1255/1230      | 230 | 188 | 65         | 60   |
| 5-25  | 852            | 355 | 1282/1257      | 230 | 188 | 66         | 61   |
| 5-27  | 906            | 355 | 1336/1311      | 230 | 188 | 67         | 62   |
| 5-28  | 933            | 355 | 1363/1338      | 230 | 188 | 67         | 62   |
| 5-29  | 1035           | 390 | 1500/1475      | 260 | 208 | 87         | 82   |
| 5-30  | 1062           | 390 | 1527/1502      | 260 | 208 | 88         | 83   |
| 5-33  | 1143           | 390 | 1608/1583      | 260 | 208 | 89         | 84   |

## CDM/CDMF 10 Installation sketch







Note1: CDM/CDMF10-15~10-22 have no oval flange pipeline connection.  
 Note2: The overall dimensions of the single-phase motor and explosive-proof motor are a little different. Please contact us for details.

## Dimensions and weights

| Model | Dimension (mm) |     |      |     |     | Weight(kg) |      |
|-------|----------------|-----|------|-----|-----|------------|------|
|       | H1             | H2  | H    | D1  | D2  | CDM        | CDMF |
| 10-1  | 267            | 245 | 592  | 170 | 142 | 31         | 29   |
| 10-2  | 267            | 245 | 592  | 170 | 142 | 32         | 30   |
| 10-3  | 297            | 245 | 622  | 170 | 142 | 35         | 33   |
| 10-4  | 337            | 290 | 707  | 190 | 155 | 41         | 39   |
| 10-5  | 367            | 290 | 737  | 190 | 155 | 45         | 43   |
| 10-6  | 397            | 290 | 767  | 190 | 155 | 46         | 44   |
| 10-7  | 437            | 345 | 862  | 197 | 165 | 57         | 55   |
| 10-8  | 467            | 345 | 892  | 197 | 165 | 58         | 56   |
| 10-9  | 497            | 355 | 932  | 230 | 188 | 65         | 63   |
| 10-10 | 527            | 355 | 962  | 230 | 188 | 66         | 64   |
| 10-11 | 557            | 355 | 992  | 230 | 188 | 67         | 65   |
| 10-12 | 665            | 355 | 1100 | 230 | 188 | 68         | 66   |
| 10-13 | 695            | 390 | 1165 | 260 | 208 | 88         | 86   |
| 10-14 | 725            | 390 | 1195 | 260 | 208 | 89         | 87   |
| 10-15 | 755            | 390 | 1225 | 260 | 208 | 90         | 88   |
| 10-16 | 785            | 390 | 1255 | 260 | 208 | 99         | 97   |
| 10-17 | 815            | 390 | 1285 | 260 | 208 | 100        | 98   |
| 10-18 | 845            | 390 | 1315 | 260 | 208 | 101        | 99   |
| 10-19 | 875            | 390 | 1345 | 260 | 208 | 102        | 100  |
| 10-20 | 905            | 390 | 1375 | 260 | 208 | 103        | 101  |
| 10-21 | 935            | 390 | 1405 | 260 | 208 | 104        | 102  |
| 10-22 | 995            | 500 | 1575 | 330 | 255 | 170        | 168  |





## CDM/CDMF 15 Installation sketch





The overall dimensions of the single-phase motor and explosive-proof motor are a little different. Please contact us for details.

## Dimensions and weights

| Model | Dimension (mm) |     |      |     |     | Weight(kg) |      |
|-------|----------------|-----|------|-----|-----|------------|------|
|       | H1             | H2  | H    | D1  | D2  | CDM        | CDMF |
| 15-1  | 297            | 245 | 632  | 170 | 142 | 40         | 33   |
| 15-2  | 307            | 290 | 687  | 190 | 155 | 48         | 41   |
| 15-3  | 362            | 345 | 797  | 197 | 165 | 59         | 52   |
| 15-4  | 407            | 355 | 852  | 230 | 188 | 66         | 59   |
| 15-5  | 452            | 355 | 897  | 230 | 188 | 68         | 61   |
| 15-6  | 575            | 390 | 1055 | 260 | 208 | 90         | 83   |
| 15-7  | 620            | 390 | 1100 | 260 | 208 | 91         | 84   |
| 15-8  | 665            | 390 | 1145 | 260 | 208 | 98         | 91   |
| 15-9  | 710            | 390 | 1190 | 260 | 208 | 99         | 92   |
| 15-10 | 785            | 500 | 175  | 330 | 255 | 157        | 150  |
| 15-11 | 830            | 500 | 1420 | 330 | 255 | 159        | 152  |
| 15-12 | 875            | 500 | 1465 | 330 | 255 | 160        | 153  |
| 15-13 | 920            | 500 | 1510 | 330 | 255 | 162        | 155  |
| 15-14 | 965            | 500 | 1555 | 330 | 255 | 163        | 156  |
| 15-15 | 1010           | 500 | 1600 | 330 | 255 | 179        | 172  |
| 15-16 | 1055           | 500 | 1645 | 330 | 255 | 181        | 174  |
| 15-17 | 1100           | 500 | 1690 | 330 | 255 | 182        | 175  |
| 15-18 | 1145           | 500 | 1735 | 330 | 255 | 184        | 177  |





## CDM/CDMF 20 Installation sketch




The overall dimensions of the single-phase motor and explosive-proof motor are a little different. Please contact us for details.

## Dimensions and weights


| Model | Dimension (mm) |     |      |     |     | Weight(kg) |      |
|-------|----------------|-----|------|-----|-----|------------|------|
|       | H1             | H2  | H    | D1  | D2  | CDM        | CDMF |
| 20-1  | 297            | 245 | 632  | 170 | 142 | 40         | 33   |
| 20-2  | 307            | 290 | 687  | 190 | 155 | 48         | 41   |
| 20-3  | 362            | 355 | 807  | 230 | 188 | 66         | 59   |
| 20-4  | 485            | 390 | 965  | 260 | 208 | 88         | 81   |
| 20-5  | 530            | 390 | 1010 | 260 | 208 | 90         | 83   |
| 20-6  | 575            | 390 | 1055 | 260 | 208 | 99         | 92   |
| 20-7  | 620            | 390 | 1100 | 260 | 208 | 100        | 93   |
| 20-8  | 695            | 500 | 1285 | 330 | 255 | 167        | 160  |
| 20-10 | 785            | 500 | 1375 | 330 | 255 | 170        | 163  |
| 20-12 | 875            | 500 | 1465 | 330 | 255 | 188        | 181  |
| 20-14 | 965            | 500 | 1555 | 330 | 255 | 191        | 184  |
| 20-17 | 1100           | 550 | 1740 | 330 | 255 | 212        | 205  |



Flange PN25/DN50



## CDM/CDMF 32 Installation sketch




The overall dimensions of the single-phase motor and explosive-proof motor are a little different. Please contact us for details.

## Dimensions and weights

| Model  | Dimension (mm) |     |      |     |     | Weight(kg) |      |
|--------|----------------|-----|------|-----|-----|------------|------|
|        | H1             | H2  | H    | D1  | D2  | CDM        | CDMF |
| 32-1-1 | 329            | 290 | 724  | 190 | 155 | 66         | 54   |
| 32-1   | 329            | 290 | 724  | 190 | 155 | 68         | 56   |
| 32-2-2 | 399            | 345 | 849  | 197 | 165 | 73         | 69   |
| 32-2   | 399            | 355 | 859  | 230 | 180 | 79         | 75   |
| 32-3-2 | 560            | 390 | 1055 | 260 | 208 | 102        | 98   |
| 32-3   | 560            | 390 | 1055 | 260 | 208 | 102        | 98   |
| 32-4-2 | 630            | 390 | 1125 | 260 | 208 | 113        | 109  |
| 32-4   | 630            | 390 | 1125 | 260 | 208 | 113        | 109  |
| 32-5-2 | 730            | 500 | 1335 | 330 | 255 | 184        | 179  |
| 32-5   | 730            | 500 | 1335 | 330 | 255 | 184        | 179  |
| 32-6-2 | 800            | 500 | 1405 | 330 | 255 | 186        | 182  |
| 32-6   | 800            | 500 | 1405 | 330 | 255 | 186        | 182  |
| 32-7-2 | 870            | 500 | 1475 | 330 | 255 | 204        | 200  |
| 32-7   | 870            | 500 | 1475 | 330 | 255 | 204        | 200  |
| 32-8-2 | 940            | 500 | 1545 | 330 | 255 | 207        | 203  |
| 32-8   | 940            | 500 | 1545 | 330 | 255 | 207        | 203  |

| Model   | Dimension (mm) |     |      |     |     | Weight(kg) |      |
|---------|----------------|-----|------|-----|-----|------------|------|
|         | H1             | H2  | H    | D1  | D2  | CDM        | CDMF |
| 32-9-2  | 1010           | 550 | 1665 | 330 | 255 | 218        | 214  |
| 32-9    | 1010           | 550 | 1665 | 330 | 255 | 218        | 214  |
| 32-10-2 | 1080           | 550 | 1735 | 330 | 255 | 221        | 217  |
| 32-10   | 1080           | 550 | 1735 | 330 | 255 | 221        | 217  |
| 32-11-2 | 1150           | 575 | 1830 | 360 | 285 | 277        | 272  |
| 32-11   | 1150           | 575 | 1830 | 260 | 285 | 277        | 272  |
| 32-12-2 | 1220           | 575 | 1900 | 360 | 285 | 280        | 275  |
| 32-12   | 1220           | 575 | 1900 | 360 | 285 | 280        | 275  |
| 32-13-2 | 1290           | 650 | 2045 | 400 | 310 | 343        | 339  |
| 32-13   | 1290           | 650 | 2045 | 400 | 310 | 343        | 339  |
| 32-14-2 | 1360           | 650 | 2115 | 400 | 310 | 346        | 342  |
| 32-14   | 1360           | 650 | 2115 | 400 | 310 | 346        | 342  |
| 32-15-2 | 1430           | 650 | 2185 | 400 | 310 | 349        | 345  |
| 32-15   | 1430           | 650 | 2185 | 400 | 310 | 349        | 345  |
| 32-16-2 | 1500           | 650 | 2255 | 400 | 310 | 352        | 347  |
| 32-16   | 1500           | 650 | 2255 | 400 | 310 | 352        | 347  |

## CDM/CDMF 42 Installation sketch



The overall dimensions of the single-phase motor and explosive-proof motor are a little different. Please contact us for details.


## Dimensions and weights

| Model  | Dimension (mm) |     |      |     |     | Weight(kg) |      |
|--------|----------------|-----|------|-----|-----|------------|------|
|        | H1             | H2  | H    | D1  | D2  | CDM        | CDMF |
| 42-1-1 | 350            | 345 | 835  | 197 | 165 | 83         | 73   |
| 42-1   | 350            | 355 | 845  | 230 | 188 | 90         | 80   |
| 42-2-2 | 521            | 390 | 1051 | 260 | 208 | 113        | 103  |
| 42-2   | 521            | 390 | 1051 | 260 | 208 | 121        | 111  |
| 42-3-2 | 631            | 500 | 1271 | 330 | 255 | 192        | 182  |
| 42-3   | 631            | 500 | 1271 | 330 | 255 | 192        | 182  |
| 42-4-2 | 711            | 500 | 1351 | 330 | 255 | 211        | 201  |
| 42-4   | 711            | 500 | 1351 | 330 | 255 | 211        | 201  |
| 42-5-2 | 791            | 550 | 1481 | 330 | 255 | 223        | 212  |
| 42-5   | 791            | 550 | 1481 | 330 | 255 | 223        | 212  |
| 42-6-2 | 871            | 575 | 1586 | 360 | 285 | 279        | 269  |
| 42-6   | 871            | 575 | 1586 | 360 | 285 | 279        | 269  |
| 42-7-2 | 951            | 650 | 1741 | 400 | 310 | 343        | 333  |

| Model   | Dimension (mm) |     |      |     |     | Weight(kg) |      |
|---------|----------------|-----|------|-----|-----|------------|------|
|         | H1             | H2  | H    | D1  | D2  | CDM        | CDMF |
| 42-7    | 951            | 650 | 1741 | 400 | 310 | 343        | 333  |
| 42-8-2  | 1031           | 650 | 1821 | 400 | 310 | 347        | 337  |
| 42-8    | 1031           | 650 | 1821 | 400 | 310 | 347        | 337  |
| 42-9-2  | 1111           | 650 | 1901 | 400 | 310 | 350        | 340  |
| 42-9    | 1111           | 650 | 1901 | 400 | 310 | 370        | 360  |
| 42-10-2 | 1191           | 650 | 1981 | 400 | 310 | 374        | 364  |
| 42-10   | 1191           | 650 | 1981 | 400 | 310 | 374        | 364  |
| 42-11-2 | 1271           | 685 | 2096 | 450 | 345 | 477        | 467  |
| 42-11   | 1271           | 685 | 2096 | 450 | 345 | 477        | 467  |
| 42-12-2 | 1351           | 685 | 2176 | 450 | 345 | 481        | 471  |
| 42-12   | 1351           | 685 | 2176 | 450 | 345 | 481        | 471  |
| 42-13-2 | 1431           | 685 | 2256 | 450 | 345 | 484        | 474  |



## CDM/CDMF 65 Installation sketch



The overall dimensions of the single-phase motor and explosive-proof motor are a little different. Please contact us for details.


For CDM/CDMF 65 series, PN25-40/DN100 standard flange is also available if required

## Dimensions and weights

| Model  | Dimension (mm) |     |      |     |     | Weight(kg) |      |
|--------|----------------|-----|------|-----|-----|------------|------|
|        | H1             | H2  | H    | D1  | D2  | CDM        | CDMF |
| 65-1-1 | 353            | 355 | 848  | 230 | 188 | 101        | 70   |
| 65-1   | 444            | 390 | 974  | 260 | 208 | 121        | 90   |
| 65-2-2 | 527            | 390 | 1057 | 260 | 208 | 133        | 102  |
| 65-2-1 | 557            | 500 | 1197 | 330 | 255 | 201        | 170  |
| 65-2   | 557            | 500 | 1197 | 330 | 255 | 201        | 170  |
| 65-3-2 | 640            | 500 | 1280 | 330 | 255 | 219        | 188  |
| 65-3-1 | 640            | 500 | 1280 | 330 | 255 | 219        | 188  |
| 65-3   | 640            | 550 | 1330 | 330 | 255 | 227        | 196  |
| 65-4-2 | 723            | 550 | 1413 | 330 | 255 | 231        | 200  |
| 65-4-1 | 723            | 575 | 1438 | 360 | 285 | 284        | 253  |
| 65-4   | 723            | 575 | 1438 | 360 | 285 | 284        | 253  |

| Model  | Dimension (mm) |     |      |     |     | Weight(kg) |      |
|--------|----------------|-----|------|-----|-----|------------|------|
|        | H1             | H2  | H    | D1  | D2  | CDM        | CDMF |
| 65-5-2 | 806            | 650 | 1596 | 400 | 310 | 349        | 318  |
| 65-5-1 | 806            | 650 | 1596 | 400 | 310 | 349        | 318  |
| 65-5   | 806            | 650 | 1596 | 400 | 310 | 349        | 318  |
| 65-6-2 | 889            | 650 | 1679 | 400 | 310 | 353        | 322  |
| 65-6-1 | 889            | 650 | 1679 | 400 | 310 | 373        | 342  |
| 65-6   | 889            | 650 | 1679 | 400 | 310 | 373        | 342  |
| 65-7-2 | 972            | 650 | 1762 | 400 | 310 | 377        | 346  |
| 65-7-1 | 972            | 650 | 1762 | 400 | 310 | 377        | 346  |
| 65-7   | 972            | 685 | 1797 | 460 | 340 | 477        | 446  |
| 65-8-2 | 1055           | 685 | 1880 | 460 | 340 | 481        | 450  |
| 65-8-1 | 1055           | 685 | 1880 | 460 | 340 | 481        | 450  |

## CDM/CDMF 85 Installation sketch



The overall dimensions of the single-phase motor and explosive-proof motor are a little different. Please contact us for details.


For CDM/CDMF 85 series, PN25-40/DN100 standard flange is also available if required

## Dimensions and weights

| Model  | Dimension (mm) |     |      |     |     | Weight(kg) |      |
|--------|----------------|-----|------|-----|-----|------------|------|
|        | H1             | H2  | H    | D1  | D2  | CDM        | CDMF |
| 85-1-1 | 453            | 390 | 983  | 260 | 208 | 110        | 101  |
| 85-1   | 453            | 390 | 983  | 260 | 208 | 118        | 109  |
| 85-2-2 | 575            | 500 | 1215 | 330 | 255 | 190        | 181  |
| 85-2   | 575            | 500 | 1215 | 330 | 255 | 205        | 196  |
| 85-3-2 | 667            | 550 | 1357 | 330 | 255 | 217        | 208  |
| 85-3   | 667            | 575 | 1382 | 360 | 285 | 270        | 261  |

| Model  | Dimension (mm) |     |      |     |     | Weight(kg) |      |
|--------|----------------|-----|------|-----|-----|------------|------|
|        | H1             | H2  | H    | D1  | D2  | CDM        | CDMF |
| 85-4-2 | 759            | 650 | 1549 | 400 | 310 | 335        | 326  |
| 85-4   | 759            | 650 | 1549 | 400 | 310 | 335        | 326  |
| 85-5-2 | 851            | 650 | 1641 | 400 | 310 | 359        | 350  |
| 85-5   | 851            | 650 | 1641 | 400 | 310 | 359        | 350  |
| 85-6-2 | 943            | 685 | 1768 | 460 | 340 | 463        | 454  |
| 85-6   | 943            | 685 | 1768 | 460 | 340 | 463        | 454  |

## CDM/CDMF 120 Installation sketch




The overall dimensions of the single-phase motor and explosive-proof motor are a little different. Please contact us for details.

## Dimensions and weights

| Model   | Dimension (mm) |     |      |     |     | Weight(kg) |      |
|---------|----------------|-----|------|-----|-----|------------|------|
|         | H1             | H2  | H    | D1  | D2  | CDM        | CDMF |
| 120-1   | 660            | 500 | 1340 | 330 | 255 | 226        | 213  |
| 120-2-2 | 820            | 500 | 1500 | 330 | 255 | 250        | 237  |
| 120-2-1 | 820            | 550 | 1550 | 330 | 255 | 263        | 250  |
| 120-2   | 820            | 575 | 1575 | 360 | 285 | 310        | 297  |
| 120-3-2 | 980            | 650 | 1810 | 400 | 310 | 375        | 362  |
| 120-3-1 | 980            | 650 | 1810 | 400 | 310 | 375        | 362  |
| 120-3   | 980            | 650 | 1810 | 400 | 310 | 375        | 362  |
| 120-4-2 | 1140           | 650 | 1970 | 400 | 310 | 405        | 392  |
| 120-4-1 | 1140           | 650 | 1970 | 400 | 310 | 405        | 392  |
| 120-4   | 1140           | 685 | 2005 | 460 | 340 | 501        | 488  |

| Model   | Dimension (mm) |     |      |     |     | Weight(kg) |      |
|---------|----------------|-----|------|-----|-----|------------|------|
|         | H1             | H2  | H    | D1  | D2  | CDM        | CDMF |
| 120-5-2 | 1300           | 685 | 2165 | 460 | 340 | 509        | 496  |
| 120-5-1 | 1300           | 685 | 2165 | 460 | 340 | 509        | 496  |
| 120-5   | 1330           | 760 | 2270 | 540 | 370 | 632        | 619  |
| 120-6-2 | 1490           | 760 | 2430 | 540 | 370 | 641        | 628  |
| 120-6-1 | 1490           | 760 | 2430 | 540 | 370 | 641        | 628  |
| 120-6   | 1490           | 845 | 2515 | 580 | 410 | 757        | 744  |
| 120-7-2 | 1650           | 845 | 2675 | 580 | 410 | 766        | 753  |
| 120-7-1 | 1650           | 845 | 2675 | 580 | 410 | 766        | 753  |
| 120-7   | 1650           | 845 | 2675 | 580 | 410 | 766        | 753  |

## CDM/CDMF 150 Installation sketch




The overall dimensions of the single-phase motor and explosive-proof motor are a little different. Please contact us for details.

## Dimensions and weights

| Model   | Dimension (mm) |     |      |     |     | Weight(kg) |      |
|---------|----------------|-----|------|-----|-----|------------|------|
|         | H1             | H2  | H    | D1  | D2  | CDM        | CDMF |
| 150-1-1 | 660            | 500 | 1340 | 330 | 255 | 227        | 214  |
| 150-1   | 660            | 500 | 1340 | 330 | 255 | 240        | 227  |
| 150-2-2 | 820            | 550 | 1550 | 330 | 255 | 263        | 250  |
| 150-2-1 | 820            | 575 | 1575 | 363 | 285 | 311        | 295  |
| 150-2   | 820            | 650 | 1650 | 400 | 310 | 364        | 351  |
| 150-3-2 | 980            | 650 | 1810 | 400 | 310 | 374        | 361  |
| 150-3-1 | 980            | 650 | 1810 | 400 | 310 | 395        | 382  |
| 150-3   | 980            | 650 | 1810 | 400 | 310 | 395        | 382  |
| 150-4-2 | 1140           | 685 | 2005 | 460 | 340 | 502        | 489  |

| Model   | Dimension (mm) |     |      |     |     | Weight(kg) |      |
|---------|----------------|-----|------|-----|-----|------------|------|
|         | H1             | H2  | H    | D1  | D2  | CDM        | CDMF |
| 150-4-1 | 1140           | 685 | 2005 | 460 | 340 | 502        | 489  |
| 150-4   | 1170           | 760 | 2110 | 540 | 370 | 625        | 612  |
| 150-5-2 | 1330           | 760 | 2270 | 540 | 370 | 636        | 623  |
| 150-5-1 | 1330           | 845 | 2355 | 580 | 410 | 752        | 739  |
| 150-5   | 1330           | 845 | 2355 | 580 | 410 | 752        | 739  |
| 150-6-2 | 1490           | 845 | 2515 | 580 | 410 | 762        | 749  |
| 150-6-1 | 1490           | 845 | 2515 | 580 | 410 | 762        | 749  |
| 150-6   | 1490           | 845 | 2515 | 580 | 410 | 762        | 749  |

## CDM/CDMF 200 Installation sketch



The overall dimensions of the single-phase motor and explosive-proof motor are a little different. Please contact us for details.

## Dimensions and weights

| Model     | Dimension (mm) |     |      |     |     | Weight(kg) |      |
|-----------|----------------|-----|------|-----|-----|------------|------|
|           | H1             | H2  | H    | D1  | D2  | CDM        | CDMF |
| 200-1-B   | 680            | 550 | 1430 | 330 | 255 | 344        | 314  |
| 200-1-A   | 680            | 575 | 1455 | 360 | 285 | 380        | 350  |
| 200-1     | 680            | 650 | 1530 | 400 | 310 | 437        | 407  |
| 200-2-2B  | 874            | 650 | 1724 | 400 | 310 | 481        | 451  |
| 200-2-2A  | 874            | 685 | 1759 | 460 | 340 | 536        | 506  |
| 200-2-A   | 904            | 760 | 1864 | 540 | 370 | 631        | 601  |
| 200-2     | 904            | 845 | 1864 | 540 | 370 | 631        | 601  |
| 200-3-2B  | 1098           | 845 | 2143 | 580 | 410 | 784        | 754  |
| 200-3-A-B | 1098           | 845 | 2143 | 580 | 410 | 784        | 754  |

| Model    | Dimension (mm) |      |      |     |     | Weight(kg) |      |
|----------|----------------|------|------|-----|-----|------------|------|
|          | H1             | H2   | H    | D1  | D2  | CDM        | CDMF |
| 200-3-2A | 1098           | 845  | 2143 | 580 | 410 | 784        | 754  |
| 200-3-B  | 1098           | 845  | 2143 | 580 | 410 | 784        | 754  |
| 200-3-A  | 1098           | 895  | 2143 | 580 | 410 | 784        | 754  |
| 200-3    | 1098           | 895  | 2193 | 580 | 410 | 853        | 823  |
| 200-4-2B | 1292           | 1140 | 2632 | 580 | 410 | 866        | 836  |
| 200-4-2A | 1292           | 1140 | 2632 | 645 | 550 | 1205       | 1175 |
| 200-4-A  | 1292           | 1140 | 2632 | 645 | 550 | 1205       | 1175 |
| 200-4    | 1292           | 1140 | 2632 | 645 | 550 | 1205       | 1175 |

# MEMO

[illegible]

This image shows a full page of white paper with horizontal dotted lines. The lines are evenly spaced and run across the width of the page, providing a guide for handwriting practice. There are no margins, text, or other markings on the page.

This image shows a full page of white paper with horizontal dotted lines. The lines are evenly spaced and run across the width of the page, providing a guide for handwriting practice. There are no margins, text, or other markings on the page.



## **Nanfang Pump Industry Co.,Ltd.**

CNP Headquarter

Address:Renhe Town, Hangzhou, China

Post code:311107

Tel:+86 571 88637351, +86 571 86397872

Fax:+86 571 86397809

E-mail:info@nanfang-pump.com

Http://www.cnppump.com



E 191002  
Code 1500077598  
subject to amendments

